

TEKNOCARE 4250-00

Surface Maintenance

TEKNOCARE 4250-00 is an aqueous product for renovation of dim surfaces of wood designated for exterior use, such as windows and doors.



TECHNICAL DATA

| | |
|--|---|
| Fields of application | Exterior doors, Windows |
| Recommended substrate | Hardwood, Softwood |
| Volatile organic compound (VOC) | Approx. 11 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet. |
| Colours | Colourless. |
| Thinner | The product is delivered ready for use. |
| Storage | Storage temperature is +5°C - +30°C. Shelf life in unopened containers: See "Best before date" on the label. Keep containers tightly closed after use. |
| Packaging | 0.5 l |

DIRECTION FOR USE

| | |
|-------------------------------|---|
| Surface preparation | The surface must be clean and free of dust, insects, and other pollutants that could serve as a basis for infestation by algae and fungi. Cleaning is done with TEKNOCLEAN 1956-00. |
| Application method | Brush, Cloth |
| Application conditions | The surface to be treated must be dry. The moisture content of the wood is to be below 20%. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5°C and the relative air humidity below 80%. Avoid application in direct sunlight. |
| Cleaning | Water. |

HEALTH AND SAFETY

Safety and precaution measures See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.