

TEKNOCOAT AQUA PRIMER 1866-11

Water-borne primer

Water-borne pigmented primer. For wood panels and fibreboards. Suitable for vertical application. Suitable for line-application. Only for interior use.

Good filling properties. Good levelling. Good sanding properties. Fast-drying.



TECHNICAL DATA

Fields of application	Furniture, Kitchen, Interior doors, Ceilings, Panels, Mouldings
Recommended substrate	Chipboard, MDF, Softwood, Hardwood, HDF, Masonite, Fibreboard
Solids	Approx. 36% by volume Approx. 54% by weight
Volatile organic compound (VOC)	Approx. 64 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Colours	White.
Thinner	Water.
Density	Approx. 1.37 kg/l
Storage	Protected against frost and not above +30°C. Keep containers tightly closed after use. The storage stability is shown on the label.
Packaging	Available in a range of standard pack sizes.

DIRECTION FOR USE

Surface preparation	The surface should be well smoothed to reduce rising of wood fibres. Sanding is recommended.
Application method	Airless spraying, Air-assisted airless spraying, Conventional spraying
Application	Stir the product homogeneous before use.
Drying time	+20°C / 50% RH
- dry to handle	1 h
- fit for sanding	2 h
- forced drying	+50°C / 50% RH - dry to handle: 20 min. after cooling - fit for sanding: 20 min. after cooling
Coating system	TEKNOCOAT AQUA PRIMER 1866-11 is normally applied in two layers. Best result when force dried. Overcoating with water-borne topcoats.

Cleaning

Water, TEKNOCLEAN 1949-00.

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.