

TEKNOCRAFT OIL 9610-15

1 and 2C solvent-borne oil with a matt appearance



TECHNICAL DATA

Fields of application	Floors, Furniture, Interior doors
Recommended substrate	Veneer, Wood
Solids	Approx. 36% by weight
Theoretical spreading rate	75 g/m ² ; 13.3 m ² /kg
Colours	Colourless.
Gloss (60°)	15
Hardener	10% TEKNOCRAFT HARDENER 9940-99 can be added to improve mechanical and chemical resistance.
Mixing ratio (A:B)	10:1 parts by volume
Pot life, +23 °C	4 h
Density	Approx. 0.9 g/ml
Storage	Storage temperature is +5 °C - +30 °C.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand
Application method	Smooth roller, Cloth Hazard warning: Pads and cloths soaked in oil can spontaneously combust under certain conditions and should therefore be kept in a metal bin with a lid until they are disposed of correctly.
Application	Stir or shake the product well for several minutes before use, if necessary by machine.
Application conditions	Recommended temperature for surroundings and product: +15 °C-25 °C. Do not apply below +10 °C. Ideal surface and object temperature for application: +18 °C-22 °C. Avoid application in direct sunlight. Underfloor heating systems must be adjusted well in advance.

Drying time	+23 °C / 50% RH (dry film 20 µm)
- dust free	3 h
- overcoatable	8 (12) h
- fit for sanding	3 h
- through dry	7 days
Cleaning	Wash the equipment immediately after use.

HEALTH AND SAFETY

Safety and precaution measures See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.