

TEKNOPAINT PRIMER 5105

Primer

TEKNOPAINT PRIMER 5105 is a very quick-drying matt water-borne primer.

Used to prime different types of mineral based board materials, such as fibre-cement boards and fibreboards. It is suitable for boards used indoors and outdoors. The paint provides a surface with good mechanical and weather resistance, that can be painted with different types of top coats. Always consult the manufacturer before starting the application.



TECHNICAL DATA

Solids	60 ±2 % by volume
Total mass of solids	Approx. 1300 g/l
Volatile organic compound (VOC)	Approx. 10 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Film thickness	First application about 100 g/m ² , depending on e.g. the substrate. Second application about 50 g/m ² , depending on e.g. the substrate. The values depend on the quality and type of the board and material loss at application.
Colours	White. Can be Teknomix tinted to light colours (near the top coat shade).
Gloss (60°)	Matt
Thinner	Water.
Storage	The storage stability is shown on the label. Store in a cool place and in tightly closed containers.

DIRECTION FOR USE

Application method	Roller
Thinning	The paint is supplied ready for application. Possible need for thinning is to be tested before use.
Top coating and suitable top coats	AQUA FASAD 5120 or TEKNOPAINT 150 TX, intended for application by spray, are especially well suited as top coats for line-painting.

HEALTH AND SAFETY

Safety and precaution measures	See safety data sheet.
---------------------------------------	------------------------

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.