

TEKNOTYRE AQUA 300-00

Dispersion paint

TEKNOTYRE AQUA 300-00 is a water-borne, air-drying dispersion-based paint for tyres.

TEKNOTYRE AQUA 300-00 is used for creating a surface finish on old or retreaded rubber tyres.

Effectively hides colour and gloss differences on the tyre and gives a smooth surface finish. TEKNOTYRE AQUA 300-00 is used on tyres to be painted after vulcanizing.



TECHNICAL DATA

Solids	12 ±2% by volume
Total mass of solids	Approx. 180 g/l
Volatile organic compound (VOC)	Approx. 6 g/l (DIRECTIVE 2010/75/EU) See safety data sheet. The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Practical spreading rate	approx. 12 m ² /l.
Colours	Black.
Gloss (60°)	Matt
Thinner	Water.
Storage	Must not freeze. Most suitable storage temperature is +5°C - +25°C.

DIRECTION FOR USE

Surface preparation	The surfaces must be free from oil, grease and other impurities.
Application method	Brush, Sponge, Spray
Application conditions	The surface to be treated has to be dry. The temperature of the air, the surface and the paint shall be above +15°C and the relative humidity of the air below 60%.
Drying time	+23°C / 50% RH (dry film 10 µm)
- touch dry	approx. 45 min. Note: Thick layers and/or low temperatures prolong the drying time.
Cleaning	Water.

HEALTH AND SAFETY

Safety and precaution measures	See safety data sheet.
---------------------------------------	------------------------

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.