

VISASOL - BASE T

Water-borne transparent paint

VISASOL - BASE T is a water-borne transparent paint.

Intended for use on external wood and plywood surfaces.

Before using the product, the manufacturer should be contacted to check the suitability of the product for the object in question.



TECHNICAL DATA

Recommended substrate	Plywood, Softwood
Binder	Acrylate
Solids	Approx. 15% by volume
Total mass of solids	Approx. 180 g/l
Volatile organic compound (VOC)	Approx. 2 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Colours	Clear.
Tinting system	Teknomix
Thinner	Water.
Storage	The storage stability is shown on the label. Store in a tightly closed container. The best storage temperature is +10°C - +25°C. Must not freeze.

DIRECTION FOR USE

Surface preparation	The surface must be clean and dry. The moisture content of the wood is to be below 20%.
Application method	Dipping, Brush, Roller, Spray
Application	Stir thoroughly before use. Dilute by adding 50 - 100% water depending on the application method and area where used.
Application conditions	During the application and drying period the temperature of the ambient air, the surface and the product shall be above +15°C and the relative air humidity below 80%.

Drying time	+23 °C / 50% RH
- dust free	45 min
- touch dry	1 h
- overcoatable	3 h
	Increase in film thickness and rise in the relative humidity of the air in the drying space usually slow down the drying process.
Cleaning	Water.

HEALTH AND SAFETY

Safety and precaution measures See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.