

# WOODEX PREMIUM

## Long-lasting wood stain

Water-borne, transparent wood stain for outdoor use. WOODEX PREMIUM Long-lasting wood stain is designed for superior protection against weather conditions prolonging maintenance interval up to two to three times longer in comparison with conventional wood stain products.



It is easy to apply – no dripping or sagging.

Protects wooden surfaces from moisture, soiling and when tinted from UV radiation of the sun. Can be tinted to Teknos translucent colours.

Use: New unpainted wood and wood previously treated with wood stain, e.g. walls, doors, window frames, fences and poles. Recommended especially for log surfaces.

It is not recommended to use WOODEX PREMIUM untinted since tinting protects wood from turning grey due to UV radiation of the sun.



## TECHNICAL DATA

<b>Fields of application</b>	Exterior doors, Fences, Outdoor wall, Windows
<b>Recommended substrate</b>	Fine-sawn wood, Log, Planed wood, Wood, Wood stain
<b>Solids</b>	Approx. 23% by volume
<b>Volatile organic compound (VOC)</b>	EU VOC limit value (kat A/e): 130 g/l. The product's VOC: max. 130 g/l.
<b>Practical spreading rate</b>	Sawn timber: 5 - 8 m <sup>2</sup> /l. Planed timber and log: 8 - 12 m <sup>2</sup> /l.
<b>Colours</b>	Clear, to be tinted to translucent shades. The final colour will be visible when the surface has dried.
<b>Tinting system</b>	Teknomix
<b>Gloss (60°)</b>	Matt
<b>Density</b>	Approx. 1 g/ml
<b>Storage</b>	Must not freeze.
<b>Packaging</b>	0.9 l, 2.7 l, 9 l. Availability varies by country.

## DIRECTION FOR USE

<b>Surface preparation</b>	<p>Remove all loose matter, dirt and dust with wire-brush, scrubbing brush or scraper.</p> <p>Coat untreated wooden surface with clear wood preservative from the WOODEX series. Allow to dry for one day.</p> <p>Wash dirty and/or mildewed surfaces with RENSA FACADE facade cleaner. Rinse the surfaces thoroughly with water and allow to dry.</p>
<b>Application method</b>	Brush, Spray
<b>Application</b>	<p>Stir thoroughly before use. Reserve a sufficient amount of wood stain in the same vessel for each uniform surface, to avoid colour differences. The wood stain must also be stirred now and then in the course of work.</p> <p>Coat untreated wood twice with WOODEX PREMIUM to achieve longer maintenance interval. The wood stain is applied evenly and continuously on the whole length of the beam or timber to avoid making restart points. Treat end grain with special care. Brush application is recommended for the first coat. When spray is used, the surface is finished by smoothing with a brush.</p> <p>We do not recommend untinted product is used.</p> <p>Maintenance painting for wooden surfaces treated with WOODEX PREMIUM may be made with Teknos's water-borne wood stains as well as with house paints.</p> <p>Not suitable for use in greenhouses, hotbeds or shelters for livestock.</p>
<b>Application conditions</b>	The surface to be treated must be dry. The moisture content of the wood is to be below 20%. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5 °C and the relative air humidity below 80%. Avoid application in direct sunlight.
<b>Drying time</b>	+23 °C / 50% RH
<b>- overcoatable</b>	2 h The drying process will be slower in cold and/or damp.
<b>Resistance</b>	Weather resistance: Excellent.
<b>Cleaning</b>	Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

## HEALTH AND SAFETY

**Safety and precaution measures** See safety data sheet.

**Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091**

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.