

TAPETTIPOHJAMAALI

wallpaper primer

| | |
|---|--|
| PRODUCT TYPE | Water-borne white acrylate dispersion paint for indoor use. Finish: full-matt. The product has been classified to Group M1 in Emission Classification of building materials. |
| USAGE | For priming on new and previously painted concrete, filler and building board surfaces that will be covered with paper, vinyl or fibre based wallpaper, as well as for fastening and priming of fibreglass cloth. Ready-to-use fillers from TEKNOSPRO series or other fillers which don't easily dissolve in water after drying are recommended for surfaces to be wallpapered. |
| <hr/> | |
| TECHNICAL DATA | |
| Solids | About 34 % by volume |
| Volatile organic compound (VOC) | EU VOC limit value (kat A/a): 30 g/l. The product's VOC: max. 30 g/l. |
| Practical spreading rate | 4 - 8 m ² /l depending on the absorbency of the substrate |
| Density | abt. 1.3 g/ml |
| Drying time at +23°C / 50% RH - dust free - fit for wallpapering | after ½ h the following day The drying will be slowed down if the air is cool and/or humid. |
| Thinner, clean up | Water. Wash the equipment immediately after use with detergent and warm water. |
| Finish | Full-matt |
| Colours | White |
| Washability and wear resistance | Wet scrub resistance, class 2 according to EN 13300 (ISO 11998). |
| Packages (availability varies by country) | White: 2,7 L, 9 L |
| <hr/> | |
| SAFETY MARKINGS | See Safety Data Sheet. |

DIRECTION FOR USE**Surface preparation**

Clean the surface from dirt and dust.
Wash previously painted, dirty surfaces with RENSA SUPER paint cleaner.
Matt down hard or gloss surfaces by sanding and thereafter remove the dust.
For smoothing of irregularities in the surface choose a suitable stopper from the TEKNOSPRO series. The dried stopper is sanded down and the dust removed.

Application

Before use stir the paint thoroughly.
Apply by roller, spray or brush.
Recommended nozzle size for airless spray is 0.017 - 0.021".

Conditions

The surface to be painted must be dry. During the application and drying period the temperature of the ambient air, the surface and the paint shall be above +5°C and the relative air humidity below 80%. Drying is faster in low air humidity and/or above + 21°C.

Taking into use

The surface painted with TAPETTIPOHJAMAALI can be wallpapered and/or top coated under normal conditions the following day.

Storage

Must not freeze.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_1917_Tuoteseloste.pdf