
SILORA MIKRODISPERS
dispersion priming agent

PAINT TYPE Transparent, water-borne and binding dispersion priming agent for indoor and outdoor use.

USAGE Can be used on new, mineral-based, absorbing substrates, such as untreated sand filler surfaces, plaster, concrete and gypsum plates.

TECHNICAL DATA

Solids About 17 % by volume

Volatile organic compound (VOC) EU VOC limit value (kat A/h): 30 g/l 2010. The product's VOC: max. 30 g/l.

Practical spreading rate 4 - 8 m²/l depending on the substrate

Density abt. 1.0 g/ml

Drying time at +23°C / 50% RH

- dry to handle after 2 hours

- through dry after 8 hours

Overcoatable after 12 h

Thinner, clean up Water. Wash the equipment immediately after use with detergent and warm water.

Colours Transparent with blue indicator agent.

DIRECTION FOR USE**Surface preparation**

Clean new surfaces from dust and dirt.

Application

Stir the paint well and apply 1-2 coats with brush, roller or spray. If required, SILORA MIKRODISPERS can be diluted up to 1 : 1 with water. SILORA MIKRODISPERS shall be entirely absorbed into the substrate and shall form no glossy film on the surface.

Application conditions

The surface to be painted has to be dry. During the application and drying period the temperature of the ambient air, the surface and the paint shall be above +5°C and the relative air humidity below 80%.

STORAGE

MUST NOT FREEZE.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.
