

TECHNICAL DATA SHEET

3 02.09.2014

NICOLUX 1262-11 Nicolux Lacquer 1262-11

PAINT TYPE	One component acid curing lacquer.			
USE	Industrial surface treatment of furniture and other wooden substrates.			
SPECIAL PROPERTIES	Quick drying lacquer. The lacquer provides a pleasant and smooth surface.			
TECHNICAL DATA				
Gloss	25, 40 and 90			
Delivery viscosity	50-55 s DIN 4 at 20 °C			
Specific gravity	Approx. 0.94 kg/l			
Solids, weight	Approx. 27 %			
Total mass of solids	Approx. 324 g/l			
Volatile organic compound (VOC)	See Safety Data Sheet.			
Storage	Storage: See label. Store in a tightly closed container.			
Application method	Spraying, curtain coating.			
Drying method	Air, oven drying			
Furniture test	Field of application Basic demands High demands Extra high demands			
	I Chairs/beds/shelves X			
	II Tables X			
	III Less exposed X			

DIRECTIONS FOR USE

Application data	mixing ratio: Spraying: Curtain coating:	10 parts lacquer 2.5 part TEKNOSOLV 1181 1 part TEKNOSOLV 1181			
Drying	At RH 55 %	20 °C	40 °C	60 °C	
	For sanding: For stacking:	2 hours 3 hours	1 hour 1.5 hour	0.5 hour 1 hour	
	The drying times are based on an applied amount of 100 g wet lacquer per m ² . After forced drying the substrates should be cooled to a temperature below 30 °C before stacking.				
Recommended amount to be applied	2 x 100 g/m²				
Cleaning	TEKNOSOLV 1181				
HEALTH AND SAFETY	See Safety Data Sheet.				
ADDITIONAL INFORMATION	Stir well before use. Should not be applied or left to dry at temperatures below 1 8°C. Should not be applied or left to dry at a relative humidity above 70 %.				

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.