

TEKNOFLOOR STRIPE

Line marking paint for sport courts

PRODUCT TYPE	Water-borne acrylate paint for line marking in indoor sport courts. The product has been classified in Emission Classification of building materials to Group M1 .
USAGE	TEKNOFLOOR STRIPE is suitable for painting of line markings for indoor sport courts. Paint is applied on a primer lacquer or between top coats. Suitable topcoats are KALLE PRO and OPAL parquet lacquers.
<hr/>	
TECHNICAL DATA	
Solids	About 38 % by volume
Volatile organic compound (VOC)	EU VOC limit value (kat A/i): 140 g/l. The product's VOC: max. 140 g/l.
Practical spreading rate	One coat: 10 - 12 m ² /l / abt. 200 m/50 mm line width
Density	abt. 1.3 g/ml
Drying time at +23°C / 50% RH - dust free - overvarnishable and overcoatable	after 1 hour after 2 hours The drying process will be slower in cold and/or damp.
Thinner, clean up	Water. Wash the equipment immediately after use with warm water and RENSA BRUSH brush cleaner.
Finish	Semi-matt
Colours	Base paints 1 and 3. The product is included in the Teknomix tinting system.
Packages (availability varies by country)	Base paint 1 and 3: 2,7 L
SAFETY MARKINGS	See Safety Data Sheet.

DIRECTION FOR USE**Surface preparation**

Wooden surface to be treated is cleaned from dirt and dust.

Application

Before use stir the paint thoroughly.

The paint can be diluted with water, if required, but dilution may impair the coverage of the paint.

Apply by roller, brush, sponge or spray.

Paint can be applied twice, if needed.

Lines can be applied on a primer lacquer or between topcoats. If the lines are applied between topcoats the first topcoat layer needs to be intersanded with grit n:o 120-150 and vacuum-cleaned before painting the lines.

If the lines are marked with a masking tape, the chosen tape must not leave any glue residues. It's recommended to remove the masking tape immediately after the application.

Application conditions

The surface to be painted has to be dry. The temperature of the air, the surface and the paint shall be +18 - +25°C and the relative air humidity 35 - 65% during the application and drying period.

ADDITIONAL INFORMATION

Storage time: in unopened containers, above +1°C, for 2 years.

MUST NOT FREEZE.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_2426_Tuoteseloste.pdf