
PRODUCT TYPE	Water-borne, ready to use putty for parquet and wooden floors. The product has been classified to Group M1 in Emission Classification of building materials. The product has been awarded the Key Flag Symbol (Avainlippu), marking Finnish origin.
USAGE	For filling gaps in parquet and wooden floors before sanding and applying water-borne primer or topcoat.
<hr/>	
TECHNICAL DATA	
Solids	About 62 % by volume
Volatile organic compound (VOC)	The product is not included in the EU VOC directive.
Practical spreading rate	abt. 8 m ² /l, depending on the amount of the gaps
Density	abt. 1.5 g/ml
Drying time, +20°C / RH 50 %	15 - 30 minutes, wider gaps 1 day The drying process will be slower in cold and/or damp.
Washing the equipment	Wash the equipment immediately after use with water and RENSA BRUSH brush cleaner.
Colours	Birch and oak
Packages (availability varies by country)	1 L, 10 L
SAFETY MARKINGS	See Safety Data Sheet.

DIRECTION FOR USE**Surface preparation and application**

The wood surface must be dry, well sanded and free from sanding dust and other dirt.

Mix the putty in the container with a drill paddle and pour the required amount of putty on the floor. Thin with a primer lacquer, if too thick. If too thin, add some sanding dust. Spread the putty with a steel trowel using crosswise strokes. Repeat if needed.

Application conditions

The temperature of the ambient air, the surface and the putty shall be +18 - 24°C and relative air humidity 40 - 60% during the application and drying period.

The moisture content of the wood should be 7 ± 2 % by weight.

ADDITIONAL INFORMATION

Storage time: in unopened containers, above +1°C, for 1 year.
MUST NOT FREEZE.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_2300_Tuoteseloste.pdf