
PAINT TYPE	A gloss bitumen paint based on bituminous resins.
USAGE	For painting indoors on concrete, plaster, steel, wood, wood fibre boards and asbestos cement sheetings. Especially intended to be used on lower parts of the walls in stables for animals and in stalls for calves and pigs - surfaces which get very dirty. Can also be used on manure gutters.
SPECIAL PROPERTIES	RANCH LADUGÅRDSLACK provides good resistance against manure, urine and ammonia vapours. Paint has good washability and the surface can be washed with high pressure washer.

TECHNICAL DATA

Solids	About 50 % by volume
Volatile organic compound (VOC)	EU VOC limit value (kat A/e): 400 g/l. The product's VOC: max. 400 g/l.
Practical spreading rate	5 - 7 m ² /l
Density	0,91 g/ml
Drying time +23°C, the relative air humidity 50%	
- touch dry	after 2 - 3 h
Overcoatable	after 12 h
Thinner, clean up	TEKNOSOLV 1621 (solvent naphtha)
Finish	Gloss
Colours	Black

SAFETY MARKINGS	See Safety Data Sheet.
------------------------	------------------------

DIRECTION FOR USE**Surface pretreatment and application**

Surfaces previously painted with bituminous paint can't be painted with typical paints. Water-borne paints don't adhere well to the greasy bituminous surface and the asphalt bleeds through solvent-borne paints and causes discolouration on the surface.

Unpainted surfaces: Clean the surface from loose material. If the surface is mildewed, clean with RENSA FACADE facade cleaner.

Old unpainted surfaces are washed with pressure washer and RENSA FACADE facade cleaner and then rinsed thoroughly with water. Prime the surface with RANCH LADUGÅRDSLACK. For priming dilute the paint and apply only a thin layer of paint. Primed surface needs to be dry before the top coating is done, otherwise it can cause runnings. Runnings can also occur if too thick coats are applied. Top coat with undiluted paint.

Previously paint surfaces: Remove poorly adhering old paint. Wash surfaces with RENSA FACADE facade cleaner and mildewed surfaces with mildew remover and rinse thoroughly with water. After the surface has dried paint the surface with undiluted RANCH LADUGÅRDSLACK.

Stir RANCH LADUGÅRDSLACK well before use to ensure the right shade. Apply the paint with brush, roller or spray.

Application conditions

The surface to be painted must be dry.

During the application and drying period the temperature of the ambient air, the surface and the paint shall be above +5°C and the relative air humidity below 80%.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_1272_Tuoteseloste.pdf