



TEKNOSEAL 4007-00 is an aqueous product for the protection of V-joints and corner joints of new wood designated for exterior use such as windows and doors.

TECHNICAL DATA

Binder: Synthetic binder

Volatile organic compound (VOC): See Safety Data Sheet.

Colour range: White.

APPLICATION DETAILS

Pre-treatment: The wood must be clean and free from wood dust and contamination. The moisture content of the wood should be approx. 13 % and should not exceed 15 %.

All softwood and non-durable hardwood for exterior use should either be vacuum impregnated (only softwood) or treated with a wood preservative.

Application: Is applied by plastic bottle with spray nozzle. Smooth with a putty knife or the like. Possible surplus is removed.

Application conditions: The product is delivered ready for use.

Optimum temperature for products and surroundings: 18-22 °C
Do not use at temperatures below 10 °C

Optimum relative air humidity: Approx. 50 %

System treatment: Primed parts must always be protected with a topcoat treatment before they are exposed to the influence of the weather.

Drying times: Dry to recoat: Approx. ½ hour

The drying times are approximate and may vary according to wood quality, temperatures, humidity, ventilation and film thickness.

Cleaning: The equipment is cleaned with water.

HEALTH AND SAFETY See Safety Data Sheet.

ADDITIONAL INFORMATION

Pack size: 250 ml plastic bottle

Storage: The product must be stored at temperatures above 10 °C. Shelf life in unopened containers: See "Best before date" on the label. Keep containers tightly closed after use.