

**TEKNOL PUUÖLJY**  
water-based wood oil**PRODUCT TYPE**

A water-based wood oil.

**USAGE**

Used for finishing treatment on press-impregnated or heat-treated wood as well as on teak. Typical objects for use are garden furniture, fences, lattice works and doors. Protects the wood from drying, cracking and soiling. It is not suitable for green houses, hotbeds nor domestic animal shelters.

Before using the product, the manufacturer should be contacted to check the suitability of the product for the object in question.

Surfaces exposed to continuous weather strain are to be retreated once a year.

**TECHNICAL DATA****Solids**

16 % by volume

**Total mass of solids**

abt. 160 g/l

**Volatile organic compound (VOC)**

abt. 107 g/l

**Spreading rate**7 - 10 m<sup>2</sup>/l**Drying time, +23°C****- touch dry**

after 2 h

**- dry**

after 1 d

The drying time depends on the quality of the wood and quantity of application.

**Thinner, clean up**

Not to be diluted. Wash the equipment with water.

**Colours**

Clear

**SAFETY MARKINGS**

See Material Safety Data Sheet.

**PTO**

NOTE! Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned. Immersion in water is also recommended. (See Material Safety Data Sheet, paragraph 7.1.)

---

**DIRECTION FOR USE****Surface preparation**

The surface must be clean and dry.  
The moisture content of the wood is to be below 20%.

**Application conditions**

The temperature of the air, the surface and the paint shall be above +15°C and the relative humidity of the air below 80% during the time of application and drying.

**Application**

Stir Teknol Wood Oil thoroughly before use.

Apply by dipping or flow coating.

**STORAGE**

Must not freeze. The best storage temperature is between +10 - +25°C.

---

The information of this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos data sheets, material safety data sheets and system sheets are on our home pages [www.teknos.com](http://www.teknos.com).

---