



# VISASOL 200

## water-borne transparent paint

---

<b>PRODUCT TYPE</b>	VISASOL 200 is a water-borne stain.
<b>USAGE</b>	Intended use for industrial staining of plywood surfaces. The product does not contain active ingredients against blue stain or surface moulds. VISASOL 200 does not protect the plywood surface against fungal growth. Before using the product, the manufacturer should be contacted to check the suitability of the product for the object in question.

---

**TECHNICAL DATA**

<b>Solids</b>	17 % by volume
<b>Total mass of solids</b>	abt. 210 g/l
<b>Volatile organic compound (VOC)</b>	abt. 20 g/l
<b>Drying time at +23°C / 50% RH</b>	
- dust free	after 45 min
- touch dry	after 1 h
<b>Overcoatable</b>	after 3 h
	Increase in film thickness and rise in the relative humidity of the air in the drying space usually slow down the drying process.
<b>Thinner, clean up</b>	Water
<b>Colours</b>	Clear The product is included in the Teknomix tinting system.

PTO

---

**DIRECTION FOR USE****Surface preparation**

The surface must be clean and dry.  
The moisture content of the wood is to be below 20%.

**Application conditions**

The temperature of the air, the surface and the paint shall be above +15°C and the relative humidity of the air below 80% during the time of application and drying.

**Application**

Before use stir the paint thoroughly.

Apply by brush, roller, spray or dipping.

Dilute by adding 50 - 100% water depending on the application method and area where used.

**ADDITIONAL  
INFORMATION**

The storage stability is shown on the label. Store in a tightly closed can. The best storage temperature is +10°C - +25°C.

MUST NOT FREEZE.

---

The information of this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos data sheets, material safety data sheets and system sheets are on our home pages [www.teknos.com](http://www.teknos.com).

---