

---

<b>TYPE</b>	Water borne paint based on synthetic binders.
<b>USE</b>	Acoustic wood wool panels. Only for interior use.
<b>SPECIAL PROPERTIES</b>	The paint has a big penetration on porous panels and leaves the surface partially open without structure.

---

**TECHNICAL DATA**

<b>Gloss</b>	Matt.
<b>Delivery viscosity</b>	20-25 s DIN cup 6
<b>Density</b>	1.47-1.52 kg/l
<b>Solids, weight</b>	Approx. 53 % depending on the colour.
<b>Storage</b>	To be protected from frost.
<b>Application</b>	Airless spraying (may be thinned with water).
<b>Drying method</b>	Convection oven.

**INSTRUCTION FOR USE**

<b>Drying</b>	Air drying/forced drying in convection oven.
<b>Recommended amount to be applied</b>	Approx. 350 g/m <sup>2</sup>
<b>Cleaning of equipment</b>	Water.

**HEALTH AND SAFETY** See Safety Data Sheet.

---

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com).

---