

INFRALIT PE 8400-13

Polyester Powder

PAINT TYPE	INFRALIT PE 8400-13 is a powder coating based on polyester resin, which due to its special hardener is free of TGIC. At elevated temperatures the powder melts, cures and forms the final paint film.
USAGE	INFRALIT PE 8400-13 can be used for product coating within the metal industry for objects that require a weather resistant coating that will not yellow on exposure to heat or ultraviolet light. Examples of use are e.g. constructions that are permanently outdoors.
SPECIAL PROPERTIES	INFRALIT PE 8400-13 forms a mechanically and chemically resistant paint film that has anticorrosive properties. The surface retains its gloss even in outdoor conditions.

TECHNICAL DATA

Colours	Clear coat
Gloss grades	Gloss
Solids	100%
Specific gravity	Abt. 1,3 kg/dm ³
Spreading rate	6 - 10 m ² /kg depending on the film thickness
Film thickness	The recommended film thickness is 60 - 100 µm. Films that are too thick may be yellowish and dull. When the film thickness exceeds 120 µm, water that evaporates in the curing process may form holes and bubbles in the paint film.
Curing time	10 min/180°C (metal temperature).
Packages	In 15 kg packages.
Storage	In dry and cool conditions.

SAFETY PRECAUTIONS

The powder itself is non-flammable, but with air it can form an explosive mixture that in presence of adequate ignition energy ignites. The lower explosive limit for polyester powder is about 80 g/m³ (Bundesanstalt für Materialprüfung). Ventilation of the spray booth should be adjusted so that the concentration of powder in the air is less than 50% of the lower explosive limit value. On calculation of the powder concentration in the spray booth, the powder deposited on the workpiece is not taken into account.

In order to avoid the discharge of powder from the booth into adjacent working spaces, the speed of air flow in the apertures of the booth must not fall below 0.5 m/s.

Spray painters should wear dust masks and protective gloves. Any spatter of powder on the skin should be washed off with water and soap.

DIRECTION FOR USE**Surface preparation**

COLD-ROLLED SURFACES: Degrease by trichloroethylene vapour bath or alkali wash. Zinc phosphating is also required if the workpiece is destined for outdoor exposure or will be subjected to exceptional strain indoors.

ALUMINIUM SURFACES: Degrease by e.g. alkali wash. Surfaces to be exposed to severe atmospheric conditions should also be chromated.

FILM PROPERTIES

Substrate 0.8 mm thick cold-rolled steel, curing time 10 min/180°C, film thickness 70 µm:

Physical properties

Flexibility (Erichsen, ISO 1520)	7 mm
Impact resistance (Erichsen, SFS EN ISO 6272)	
- direct	40 kgcm
- reverse	40 kgcm
Pendulum hardness (König, SFS 3642)	180 s
Flexibility (SFS ISO 6860)	less than 5 mm
Adhesion (cross-cut test, EN ISO 2409)	GT 0

The information of this data sheet is normative and based on laboratory tests and practical experience. Teknos guarantees that the product quality conforms to our quality system. Teknos accepts, however, no liability for the actual application work, as this is to a great extent dependent on the conditions during handling and application. Teknos accepts no liability for any damage resulting from misapplication of the product. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_1720_Tuoteseloste.pdf