

---

<b>PRODUCT TYPE</b>	Solvent-borne wood oil for outdoor use.	
<b>USAGE</b>	Natural oil for outdoor use for protection of garden deck floors and wooden garden furniture. Other suitable objects are fences, trellises, doors and stairs. For heat-treated and press-impregnated wood and for exotic wood sorts. Applied on clean, dry wooden surface by brush, sponge or by dipping. Protects wooden surfaces from moisture, soiling and when tinted from UV radiation of the sun. Deminishes cracking of the wooden surface. For the best durability the treatment with WOODEX WOOD OIL is renewed annually. Not suitable for greenhouses, hotbeds and shelters for livestock.	
<hr/>		
<b>TECHNICAL DATA</b>		
<b>Solids</b>	About 30 % by volume	
<b>Volatile organic compound (VOC)</b>	The product is not included in the EU VOC directive.	
<b>Practical spreading rate</b>	Sawn timber	5 - 8 m <sup>2</sup> /l
	Planed timber	8 - 10 m <sup>2</sup> /l
<b>Density</b>	abt. 0.85 g/ml	
<b>Drying time, +23°C</b>		
- touch dry	after 8 hours	
- dry	after 16 hours	
	The drying process will be slower in cold and/or damp.	
<b>Thinner, clean up</b>	To be used without thinning. The equipment is washed immediately after use with TEKNOSOLV 1621 (solvent naphtha).	
<b>Finish</b>	Is absorbed into the wood and does not usually form any visible film.	
<b>Colours</b>	Clear, brown, grey and translucent colours.	
<b>Weather resistance</b>	For surfaces that are continuously exposed to weathering a renewed treatment is necessary once a year.	
<b>Packages</b> (availability varies by country)	<b>Brown</b> 0,9 L, 2,7 L, 9 L <b>Grey</b> 0,9 L, 2,7 L, 9 L <b>Clear</b> 0,9 L, 2,7 L, 9 L	

---

**SAFETY MARKINGS**

See Safety Data Sheet.

NOTE! Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers. Immersion in water is also recommended.

PTO

---

**DIRECTION FOR USE****Surface preparation**

Clean the surface to be treated. Use RENSA TERRACE deck cleaner on surfaces to be treated, when needed. Rinse the surfaces thoroughly with water and allow to dry. Remove from the surface all loose and poorly adherent old matter and fluffy top layers of the wood. We recommend that untreated wood is primed with wood preservative from WOODEX-series. Remove old paint or varnish layers before the treatment.

**Application**

Before use stir the product thoroughly down to the bottom of the can.

The product must be frequently stirred thoroughly down to the bottom of the can also during the application. Applied on the surface 1 - 2 times by brush, sponge or by dipping. Depending on the quality of the wood, the treatment is renewed. The possible excess oil is wiped off.

**Application conditions**

The surface to be treated must be dry. The relative moisture of the wood must be below 20% of the weight of the wood.

During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5 °C and the relative air humidity below 80%.

---

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages [www.teknos.com](http://www.teknos.com).

---



EN\_1704\_Tuoteseloste.pdf