

PRODUCT TYPE DONNA wood oil is a satin matt oil for wooden surfaces indoors. Provides wooden surfaces with a durable and breathable protection.

Product meets the requirements of toy safety standard EN 71-3:2013 for limit values for migration of chemical elements.

USAGE DONNA is intended for protection of wooden furniture indoors. DONNA improves wear resistance of the wooden surfaces as well as protects them from moisture and dirt. Intensifies elegantly wood's natural colour. Does not require a separate priming.

TECHNICAL DATA

Solids	About 36 % by weight
Volatile organic compound (VOC)	The product is not included in the EU VOC directive.
Practical spreading rate	Untreated smooth surface abt. 12 m ² /l
Density	abt. 0.9 g/ml
Drying time, +23°C - dust free - recoatable - fully dried	Clear after 2 hours (tinted 2 - 3 hours) Clear after 6 - 8 hours (tinted 16 hours) after 7 days The drying process will be slower in cold and/or damp.
Thinner, clean up	TEKNOSOLV 1621 (solvent naphtha)
Finish	Matt
Colours	Clear, black, white and Nordic white
Packages (availability varies by country)	Clear: 0,25 L Ready-made shades: 0,25 L

SAFETY MARKINGS

See Safety Data Sheet.
NOTE! Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers. Immersion in water is also recommended.

PTO

DIRECTION FOR USE**Surface preparation**

Clean wooden surfaces of dust and dirt. If the wooden surface has previously been oiled, the surface must be sanded bare. DONNA wood oil must always be applied to a dry, recently sanded surface.

Application

Stir well before use. Apply the oil with a brush, sponge or cloth. Apply generously both along grain direction and sideways, and allow the oil to be absorbed for a while. Wipe off any excess oil with a cloth or rub it into the wooden surface while still wet using a sponge or cloth.

Application conditions

The surface to be treated must be dry. The temperature of the ambient air, the surface and the product shall be above +10°C and the relative air humidity below 80% during the application and drying period.

STORAGE

In tightly closed packages, protected from frost

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_2325_Tuoteseloste.pdf