

2021

MAINTENANCE INSTRUCTIONS FOR FLOORS PAINTED WITH TEKNOS FLOOR PAINTS

FLOORS TREATED WITH TEKNOFLOOR AQUA FLOOR PAINT

Clean the surface with hand dishwashing detergent or all-purpose cleaner. Rinse thoroughly with water and wipe the surface and ventilate the moist air. Note! Do not use too hot water.

FLOORS PAINTED WITH TEKNOFLOOR FLOOR SOLVENT BORNE ALKYD PAINT

In case of light dirt, the same treatment as Teknofloor Aqua floor paint is used.

FLOORS PAINTED WITH TEKNOFLOOR 2K CONCRETE PAINT

Vacuuming (possible sweeping of painted surface). Washing with warm water, about 35-40°C and RENSA SUPER Paint wash. Wash the floor with cloth or mop, use a scrubbing brush on heavily soiled surfaces.

GENERALLY

Never use spirits or strong organic solvents.

Bleach may fade away some stains (used with care). Food vinegar can be used to remove rust stains. Black discolorations resulting from rubbing metal against the surface can usually be removed with a regular eraser.

Teknos Group Takkatie 3, P.O. Box 107 FI-00370 Helsinki Tel. +358 9 506 091 www.teknos.com

WE MAKE THE WORLD LAST LONGER