

METAL PAINTS THAT MATCH

Designed for small batch production with fast delivery, INFRALIT PE 8350-20 POWDER MIX is powder coating for businesses who usually coat in wet paint. Offer your customers the seamless look of metal beading matched to a window's opaque colour, guttering which blends with a garden room shade or decorative finials which top off a conservatory.

Our small batch, short turnaround powder production means that your contract powder coaters can get the job done fast, reducing downtime for the rest of the job going through your wet paint line.

POWDER MIX is highly durable and holds Class 1 Qualicoat approval for outdoor colour and gloss retention. It is easily colour matched to standard shades or a customer's particular colour choice.

SMALL BATCH ORDERING

We have an extensive colour database including RAL and NCS and can match bespoke shades with a physical sample (extended lead time). Small batch production means only ordering what you need, resulting in less waste; better for your business and the planet.

- Order in quantities as small as 5kg or up to 100kg
- Fast production (2-3 days average) to your specification
- Cures in 9-10 minutes depending on metal temperature (180-190°C)
- Smooth, semi-gloss finish after application
- Suitable for aluminium or steel surfaces

INFRALIT PE 8350-20 POWDER MIX is the easy way to complement and add value to your wood product line.

MAIN FEATURES

Qualicoat and GSB approved for durability

Small batch production from 5kg

Excellent UV and corrosion resistance

Short lead time, mixed to your specification

M1 certified as a low-emitting product



CONTACT US

Contact your local Teknos coating expert for more information.

Our mission is to extend the life of your products by providing intelligent, technically advanced paint and coating solutions for even better protection - always in close collaboraton with our customers.



PRODUCT INFORMATION

INFRALIT PE 8350-20 POWDER MIX

Small batch powder coating for exterior metal surfaces

FINISH	Opaque colours Gloss 65-85	
APPLICATION	Suitable for both corona and tribo spraying	
FILM THICKNESS	60 - 100µm	
CURING TIME	9 mins at 190°C 10 mins at 180°C	

TEKNOS GROUP OY Takkatie 3 PO Box 107 FI-00370 Helsinki T +358 9 506 091 sales@teknos.com

www.teknos.com

WE MAKE THE WORLD Last Longer



The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies

0066_ v1