

# TEKNOCLAD NOVA 3330-42



Nordic Swan Ecolabel approved coating for wooden cladding

## ENVIRONMENTALLY SENSITIVE PAINT

Designed for minimum impact on the environment, this industrial coating for cladding is highly durable and approved under the Nordic Swan Ecolabel scheme.

This approval means that you can be confident that TEKNOCLAD NOVA 3330-42:

- Meets strict environmental requirements regarding its lifecycle and contents
- Is a sustainable choice for coating wooden cladding

## WATER-BORNE AND LONG-LASTING

As well as being a sustainable coating solution, TEKNOCLAD NOVA 3330-42 demonstrates excellence in coating performance. As a direct-to-wood product it primes, is an intermediate and also topcoats, all in one can. It also repels dirt and retains its colour, protecting your cladding products and maintaining their quality appearance.

## EASY MAINTENANCE

As part of our ambition to help make the world last longer, making your cladding products last longer with good maintenance is easy for your customers.

A selection of complementary decorative paints are available from our NORDICA range. Homeowners can continue their claddings' sustainable journey by choosing Nordic Swan Ecolabel approved NORDICA CLASSIC, to maintain their wooden facades.



## MAIN FEATURES

Nordic Swan Ecolabel approved

Complementary, Ecolabelled maintenance system

All-in-one product; primer, intermediate, topcoat

Direct-to-wood application

Highly durable



## CONTACT US

Contact your local Teknos coating expert for more information.

*Our mission is to extend the life of your products by providing intelligent, technically advanced paint and coating solutions for even better protection - always in close collaboration with our customers.*



# PRODUCT INFORMATION



## TEKNOCLAD NOVA 3330-42 Nordic Swan Ecolabel approved topcoat

<b>FINISH</b>	Opaque colours and white Semi-matt
<b>APPLICATION</b>	Automatic or manual high pressure spray, Brush machine, Vacumat

## EXAMPLE COATING SYSTEM

DRYING TIMES		LAYER		PRODUCT	
Dry to handle	1 hour	1		TEKNOCLAD NOVA 3330-42	
Dry to re-coat	Next day	2		TEKNOCLAD NOVA 3330-42	

TEKNOCLAD NOVA 3330-42 is a direct-to-wood solution. To achieve additional protection against for example, wood destroying fungi, apply Teknos wood preservative TEKNOL AQUA 1410-01, as the first layer. Ask your Teknos coating expert for further information or visit [teknos.com](http://teknos.com) for full product details and Technical Data Sheets.



TEKNOS GROUP OY  
Takkatie 3  
PO Box 107  
FI-00370 Helsinki  
T +358 9 506 091  
[sales@teknos.com](mailto:sales@teknos.com)

[www.teknos.com](http://www.teknos.com)

**WE MAKE THE WORLD  
LAST LONGER**



The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies