## Teknos Technical Library



On-Site Guide

> Version 1: July 2022



## CLEANING DOORS WITH RESIDUAL AGENTS ON Surface

During Autumn and Winter, temperature fluctuations lead to condensation on windows and doors.

Dependant on the construction of the door, condensation can occur on the surface of the door blade.

In relation to this, moisture will appear on the front of the door blade and extract residues to the surface, and the phenomenon in the picture below can be observed.


The residues can be washed off by cleaning the weathered surface.

## **INSTRUCTIONS FOR CLEANING**

- 1. Use a soft cloth or a clean brush.
- 2. Dilute TEKNOCLEAN 1956 in a ratio of 1:1 with water. Let the cleaning agent work for about 5 minutes and then neutralize the treated surfaces with clear water.
- 3. Dependent on the level of residuals on the surface it may be necessary to repeat the cleaning to remove all residuals.

The cleaning has changed the surface tension of the door panels.

The condensation on the surface indicates a successful clean, as shown on the image below.



For further support, contact your local Teknos coating expert or visit **teknos.com** 



Always refer to the Technical Datasheet for full instructions on how to use Teknos products.

TEKNOS GROUP OY TAKKATIE 3, P.O.BOX 107 FI–00371 HELSINKI TEL. +358 9 506 091 SALES@TEKNOS.FI

WE MAKE THE WORLD LAST LONGER

