## **SAFETY DATA SHEET**



UVILUX 651-14120 - TRANSPARENT R4/R7

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : UVILUX 651-14120 - TRANSPARENT R4/R7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product description : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: prod-safe@teknos.com

**National contact** 

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

Telephone number: Teknos UK Limited; TEL: +44 1608 683 494; Opening hours: MON-FRI, 7am – 6pm.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H318 - Causes serious eye damage.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : Not applicable.

**Prevention**: P280 - Wear protective gloves. Wear eye or face protection.

P273 - Avoid release to the environment.

Response : P305 + P351 + P310 - IF IN EYES: Rinse cautiously with water for several minutes.

Immediately call a POISON CENTER or physician.

Storage : Not applicable.

#### SECTION 2: Hazards identification

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Hazardous ingredients** 

pipropylenglycol diacrylate

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,

3-epoxypropane, esters with acrylic acid

Methylbenzoylformiat

Supplemental label

elements

articles

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and

2.3 Other hazards

Other hazards which do not result in classification : None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥10 - <25	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
Methylbenzoylformiat	REACH #: 01-2120101338-67 EC: 239-263-3 CAS: 15206-55-0	<1	Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

UVILUX 651-14120 - TRANSPARENT R4/R7 **Label No** :31358 Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version: 1.04 2/12

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eve contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

UVILUX 651-14120 - TRANSPARENT R4/R7 **Label No** : \$\insigma 1358 **Date of issue/Date of revision** : 03/05/2021 **Date of previous issue** : 17/04/2019 **Version** : 1.04 **3/12** 

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: In a fire, decomposition may produce toxic gases/fumes.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## **6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

## 6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No : ₹1358

Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version : 1.04 4/12

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations : Not available. : Not available. **Industrial sector specific** solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

**7**-Butyl acetate

#### EH40/2005 WELs (United Kingdom (UK), 8/2018).

STEL: 966 mg/m3 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m<sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.

## procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No :31358 : 03/05/2021 Date of previous issue Version : 1.04 5/12 : 17/04/2019

Date of issue/Date of revision

## **SECTION 8: Exposure controls/personal protection**

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.
< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Refer to European Standard EN 14605 for further information on material and design requirements and test methods.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.
Colour : Colourless.
Odour : Slight
Odour threshold : Not available.
pH : Not available.
Melting point/freezing point : Not available.

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No : 3/1358

Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version : 1.04 6/12

## SECTION 9: Physical and chemical properties

Initial boiling point and

boiling range

: Not available.

Flash point

: Closed cup: >100°C

**Evaporation rate** Flammability (solid, gas) Upper/lower flammability or

: Not available. : Lower: 1.4%

: Not available.

explosive limits Vapour pressure

Solubility(ies)

Upper: 10.9% : Not available. : Not available.

Vapour density **Density** 

1.4 kg/l : Not available.

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature Decomposition temperature**  : >240°C : Not available.

**Viscosity Explosive properties** 

**Oxidising properties** 

: Not available. : Not available. : Not available.

g/l

9.2 Other information

VOC : 64 Solubility in water : Not available.

No additional information.

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
propylenglycol diacrylate	LD50 Oral	Rat	4600 mg/kg	-
n-Butyl acetate	LC50 Inhalation Vapour	Rat	0.74 mg/l	4 hours
	LD50 Dermal	Rabbit	14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

**Acute toxicity estimates** 

Not available.

#### **Irritation/Corrosion**

UVILUX 651-14120 - TRANSPARENT R4/R7 **Label No** :31358 Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version: 1.04 7/12

## SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
propylenglycol diacrylate	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	500 mg	-
n-Butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				mg	

**Conclusion/Summary** 

: Causes skin irritation.

**Sensitisation** 

**Conclusion/Summary** : May cause an allergic skin reaction.

**Mutagenicity** 

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Teratogenicity** 

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
P-Butyl acetate	Category 3	Not applicable.	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No :31358 8/12

Date of issue/Date of revision : 03/05/2021 Date of previous issue Version: 1.04 : 17/04/2019

## **SECTION 11: Toxicological information**

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
r-Butyl acetate	<u> </u>	Crustaceans - Artemia salina Fish - Pimephales promelas	48 hours 96 hours

**Conclusion/Summary**: Farmful to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: This product has not been tested for biodegradation.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylenglycol diacrylate 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2, 3-epoxypropane, esters with acrylic acid	0.01 to 0.39 1.6 to 3	-	low low
n-Butyl acetate	2.3	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No : 31358

Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version : 1.04 9/12

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue: \$\overline{08}\$0111\*

(EWC)

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for : user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

UVILUX 651-14120 - TRANSPARENT R4/R7 Label No :31358 Date of issue/Date of revision : 03/05/2021 Date of previous issue Version: 1.04 10/12 : 17/04/2019

## **SECTION 15: Regulatory information**

None of the components are listed.

Annex XVII - Restrictions on the manufacture,

placing on the market and use of certain

dangerous substances, mixtures and articles

Other EU regulations

Europe inventory : Not determined.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Irrit. 2, H315	Calculation method	
Eye Dam. 1, H318	Calculation method	
Skin Sens. 1, H317	Calculation method	
Aquatic Chronic 3, H412	Calculation method	

Full text of abbreviated H statements

UVILUX 651-14120 - TRANSPARENT R4/R7

Label No :31358

Date of issue/Date of revision : 03/05/2021 Date of previous issue : 17/04/2019 Version : 1.04 11/12

#### **SECTION 16: Other information**

<b>⊮</b> 226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Aquatic Chronic 2, H411 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Aquatic Chronic 3, H412 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 **EUH066** Repeated exposure may cause skin dryness or cracking. Eve Dam. 1, H318 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 Flam. Lig. 3, H226 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2, H315 Skin Sens. 1. H317 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE **STOT SE 3. H336** (Narcotic effects) - Category 3

Date of issue/ Date of : 03/05/2021

revision

**Date of previous issue** : 17/04/2019

Version : 1.04

JVILUX 651-14120\_TRANSPARENT R4/R7 TRANSPARENT R4/R7

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

UVILUX 651-14120 - TRANSPARENT R4/R7

\*\*Date of issue/Date of revision\*\*: 03/05/2021 \*\*Date of previous issue\*\*: 17/04/2019 \*\*Version\*\*: 1.04 \*\*12/12\*\*

\*\*Date of issue/Date of revision\*\*: 1.04 \*\*Date of previous issue\*\*: 17/04/2019 \*\*Version\*\*: 1.04 \*\*12/12\*\*

\*\*Date of issue/Date of revision\*\*: 1.04 \*\*Date of previous issue\*\*: 17/04/2019 \*\*Version\*\*: 1.04 \*\*12/12\*\*

\*\*Date of issue/Date of revision\*\*: 1.04 \*\*Date of previous issue\*\*: 17/04/2019 \*\*Version\*\*: 1.04 \*\*12/12\*\*

\*\*Date of issue/Date of revision\*\*: 1.04 \*\*Date of previous issue\*\*: 17/04/2019 \*\*Da