

TECHNICAL DATASHEET

Description : **UVILUX SEALER 244**

Product Number : **661-244-0000**

Description : Colourless acrylic UV-curable sealer for roller application in the coating process of parquet and veneered flooring panels. The product shows good sandability and sealing property.

Characteristics

Viscosity : 70 - 80 sec. in DIN 8mm at 25°C

Density : 1.3 ± 0.2 kg/l

Solid Content : 98 - 99%

VOC : Max 2%

Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Not required

Viscosity : As delivered

Film Weight : Apply 12 - 18 g/m².

Mode : Apply in roller machine.

Curing : Semi cure: 70 - 80 mJ/cm²
Full cure: 190 - 200 mJ/cm²

Substrate : The product is a specially formulated UV sealer to be applied on TEKNOS UV fillers or sealers. Please consult our technical staff prior to other applications.

TECHNICAL DATASHEET

Description : **UVILUX SEALER 244**

Product Number : **661-244-0000**

Storage

Shelf Life : 6 months

Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Cleaning : Use solvent such as butyl acetate for cleaning.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.