

TECHNICAL DATASHEET

Description : **UVILUX SEALER 251**

Product Number : **661-251-0000**

Description : UV-curable acrylic matt sealer for intermediate roller application in the coating process of parquet and veneered flooring panels. The product provides good sealer property while leaving a matt finish.

Characteristics

Viscosity : 50 - 70 sec. in DIN 6mm at 25°C

Density : 1.25 ± 0.1 kg/l

Solid Content : 98 - 99%

VOC : Max 2%

Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Not required

Viscosity : As delivered

Film Weight : Apply 12 - 15 g/m².

Mode : Apply in roller machine.

Curing : Semi-cure: 70 - 80 mJ/cm²
Surface cure: 190 - 200 mJ/cm²

Substrate : The product is a specially formulated UV sealer to be applied on TEKNOS UV fillers or sealers. Please consult our technical staff prior to other applications.

Storage

TECHNICAL DATASHEET

Description : **UVILUX SEALER 251**

Product Number : **661-251-0000**

Shelf Life : 6 months

Conditions : Protect from sunlight and frost.
To be stored at 5 - 35°C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Cleaning : Use solvent such as butyl acetate for cleaning.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.