TEKNOS (M) Sdn. Bhd. PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang,Johor, Malaysia T +60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 1 / 2

Description	: W/B TOPCOAT
Product Number	: 254-209-0001
Description	: Transparent waterborne topcoat for spray application on wood substrate and wood related substrates. It gives extra clear and matt finishing for aesthetic appearance of the coating.
Characteristics	
Viscosity	: 60 - 100 sec. in DIN 4mm at 25 ^o C.
Density	: 1.04 ± 0.02 kg/l
Solid Content	: 30 - 36%
VOC	: Max 2%
Classification	: Complies with the Environmental Protection Act of 1990.
Application	
Preparation	: Stir well and check before use.
Hardener	: Not applicable
Thinner	: Use water to adjust viscosity if required.
Viscosity	· As delivered

- Viscosity : As delivered
- *Film Weight* : Apply as per customer application.
- Mode : Spraying application with spray gun.
- *Drying* : Determined at > 30 °C and 70 % 80% relative humidity:

Drying time varies from 30 min - 2 hours.

The drying time can be reduced using special drying systems to force drying. The drying times are approximate and may vary according to wood quality, temperatures, humidity, ventilation and film thickness.

*As the layer thickness is of paramount importance for the effectiveness of the product, it is important not to sand the surface too much.

TEKNOS (M) Sdn. Bhd. PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang,Johor, Malaysia T +60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 2 / 2

Description Product Number	:	W/B TOPCOAT 254-209-0001
		Please consult our technical staff for further informations.
Substrate	:	This product is specially formulated to be applied as topcoat on Teknos Waterborne Sealers or Primers. Please consult our technical staff prior to other applications.
Storage		
Shelf Life	:	12 months
Conditions	:	The product should be stored between 5°C and 35°C. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances. Higher temperatures reduce the shelf life. Protect from sunlight and frost.
Delivery		
Packaging	:	Available in 20 kg pails.
Delivery Time	:	Please allow 6 working days of production and transportation.
Cleaning	:	Clean equipment with water immediately after use.
Precautions	:	Refer to Safety Data Sheet.
Health & Safety	:	Refer to Safety Data Sheet.