TEKNOS (M) Sdn. Bhd. PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor, Malaysia T +60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 1 / 2

Description : W/B TOPCOAT
Product Number : 257-209-8000

Description : Colourless one component waterborne-finished for brushing or

spraying application. Due to excellent leveling and clarity, the product produces a very elegant finish when applied as multi-layered coating (minimum of two layers). It can be applied on wood based

substrate like MDF, HDF and profiles.

Characteristics

Viscosity : 35 - 45 sec. in DIN 6mm at 25°C

Density : $1.04 \pm 0.02 \text{ kg/l}$

Solid Content : 36 - 42% VOC : Max 3%

Classification : Complies with the Environmental Protection Act of 1990.

Direction for Use

Preparation : Stir well and check before use.

Hardener : Not applicable

Thinner : Use water for application viscosity.

Viscosity : As delivered

Film Weight : min 50 - 100 gsm depending to substrate coverage.

Application method : Airless spraying, Airmix spraying or brushing.

Ambient condition : 28-35°C/70-80% RH

Drying condition : Surface Tack Free Time : Approx. 20 mins

Dry for Stacking : Min. 24 hours

The drying time can be reduced using special drying systems to force drying. The drying times are approximate and may vary depending on the wood quality, ambient temperatures, humidity,

ventilation and film thickness.

TEKNOS (M) Sdn. Bhd. PLO 577, Jalan Keluli 8 Kawasan Perindustrian Pasir Gudang 81700 Pasir Gudang, Johor, Malaysia T +60 7 251 5115 F +60 7 251 4115 info.malaysia@teknos.com www.teknos.my



TECHNICAL DATASHEET

Page: 2 / 2

Description : W/B TOPCOAT
Product Number : 257-209-8000

Substrate : This product is specially formulated to be applied as topcoat on

Teknos Waterborne Sealers or Primers. Please consult our technical

staff prior to other applications.

Storage

Shelf Life : 12 months

Conditions : The product should be stored between 5°C and 35°C. Keep

container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances. Higher temperatures reduce the shelf life. Protect from sunlight and frost.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : -

Cleaning : Clean equipment with water immediately after use.

Precautions : Refer to Safety Data Sheet.

Health & Safety: Refer to Safety Data Sheet.