

TECHNICAL DATASHEET

Description : **W/B SEALER**

Product Number : **261-209-1000**

Description : Acrylic waterborne primer for roller application on wood edge / level of flooring like DPL and PDL flooring. It has good wetting, fast drying properties and good water resistance.

Characteristics

Viscosity : 20 - 30 sec. in DIN 4mm at 25°C.

Density : 1.64 ± 0.02 kg/l

Solid Content : 68 - 73%

VOC : Max 2%

Pigments : Does not contain any lead, cadmium or chromate.

Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Not required

Viscosity : As delivered

Film Weight : Apply 10 - 15 g/m².

Mode : Apply in roller machine with a shore hardness of offset rollers of 40-50 (Isobutylene / Isoprene-Copolymer or EPDM-Prepolymer).

Drying : 12-15 sec at 120°C jet air with airspeed of 23 m/s.
50 sec at 150°C circulatory air with airspeed of 5-7 m/s and a circulatory to fresh air proportion 8:2.

Substrate : The product is specially formulated as Waterborne Sealer to be applied on wood edge / bevel of flooring.
Please consult our technical staff prior to other applications.

TECHNICAL DATASHEET

Description : W/B SEALER
Product Number : 261-209-1000

Storage

Shelf Life : 12 months
Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.
Delivery Time : Please allow 6 working days of production and transportation.
Quantity : Except for trial, minimum quantity is 100kg per individual product.

Cleaning : Clean equipment with water immediately after use.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.