

# TECHNICAL DATASHEET

**Description** : **W/B SEALER**

**Product Number** : **261-209-1000**

**Description** : Opaque white acrylic waterborne sealer for roller application on wood edge / level of flooring like DPL and PDL. The product provides good wetting and drying properties.

## Characteristics

*Viscosity* : 20 - 30 sec. in DIN 4mm at 25°C.

*Density* : 1.64 ± 0.02 kg/l

*Solid Content* : 68 - 73%

*VOC* : Max 2%

*Pigments* : Does not contain any lead, cadmium or chromate.

*Classification* : Complies with the Environmental Protection Act of 1990.

## Application

*Preparation* : Stir well and check before use.

*Hardener* : Not required

*Thinner* : Not required

*Viscosity* : As delivered

*Film Weight* : Apply 10 - 15 g/m<sup>2</sup>.

*Mode* : Apply in roller machine.

*Drying* :  
12-15 sec at 120°C jet air with airspeed of 23 m/s.  
50 sec at 150°C circulatory air with airspeed of 5-7 m/s and a circulatory to fresh air proportion 8:2.

**Substrate** : The product is specially formulated as Waterborne Sealer to be applied on wood edge / bevel of flooring.  
Please consult our technical staff prior to other applications.

# TECHNICAL DATASHEET

Page: 2 / 2

**Description** : W/B SEALER  
**Product Number** : 261-209-1000

## Storage

**Shelf Life** : 12 months  
**Conditions** : The product should be stored between 5°C and 35°C. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances. Higher temperatures reduce the shelf life. Protect from sunlight and frost.

## Delivery

**Packaging** : Available in 20 kg pails.  
**Delivery Time** : Please allow 6 working days of production and transportation.

**Cleaning** : Clean equipment with water immediately after use.

**Precautions** : Refer to Safety Data Sheet.

**Health & Safety** : Refer to Safety Data Sheet.