

TECHNICAL DATASHEET

Page: 1 / 2

Description : **W/B PRINTING INK HI-VISC**
Product Number : **241-202-0000**

Description : Waterborne colourless printing ink for colour matching in printing ink 241- to be applied in heavy duty printing machines on TEKNOS TREFFERT 231- waterborne basecoats. This product shows good performance in light fastness properties and free from any hazardous heavy metal.

Characteristics

Viscosity : 100 - 110 sec. in DIN 4mm at 25°C.
Density : 1.02 ± 0.02 kg/l
Solid Content : 13 - 17%
VOC : Max 3%
Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.
Hardener : Not applicable
Thinner : Use water to adjust viscosity if required.
Viscosity : As delivered
Film Weight : Not applicable.
Mode : Apply in roller machine with a shore hardness of offset rollers of 40-50 (Isobutylene / Isoprene-Copolymer or EPDM-Prepolymer).
Drying : 5 sec. at ventilated air and room temperature.

Substrate : This product is specially formulated as ink concentrate for colour matching in printing ink 241- on TEKNOS TREFFERT 231- waterborne basecoats.
Please consult our technical staff prior to others applications.

TECHNICAL DATASHEET

Page: 2 / 2

Description : **W/B PRINTING INK HI-VISC**
Product Number : **241-202-0000**

Storage

Shelf Life : 12 months
Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.
Delivery Time : Please allow 6 working days of production and transportation.
Quantity : Minimum quantity is 20 kg.

Cleaning : Clean equipment with water immediately after use.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.