

TECHNICAL DATASHEET

Page: 1 / 2

Description : **W/B TOPCOAT**

Product Number : **257-209-8000**

Description : Colourless one component waterborne-finished for brushing or spraying application. Due to excellent leveling and clarity, the product produces a very elegant finish when applied as multi-layered coating (minimum of two layers). It can be applied on wood based substrate like MDF, HDF and profiles.

Characteristics

Viscosity : 35 - 45 sec. in DIN 6mm at 25°C
Density : 1.04 ± 0.02 kg/l
Solid Content : 36 - 42%
VOC : Max 3%
Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.
Hardener : Not applicable
Thinner : Use water to adjust viscosity if required.
Viscosity : As delivered
Film Weight : Apply 80 - 100 g/m².
Drying :
12-15 sec at 120°C jet air with airspeed of 23 m/s.
50 sec at 150°C circulatory air with airspeed of 5-7 m/s and a circulatory to fresh air proportion 8:2.

Substrate : This product is specially formulated to be applied as topcoat on TEKNOS TREFFERT COATINGS Waterborne Sealers or Primers. Please consult our technical staff prior to other applications.

Storage

TECHNICAL DATASHEET

Description : **W/B TOPCOAT**

Product Number : **257-209-8000**

Shelf Life : 12 months

Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5 - 35 °C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Quantity : Except for trial, minimum quantity is 100kg per individual product.

Cleaning : Clean equipment with water immediately after use.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.