

TECHNICAL DATASHEET

Description : **W/B STAIN BASE**

Product Number : **284-209-0000**

Description : Colourless waterborne stain for spray application in the coating process of solid wood or veneered furniture components. The product shows excellent colouring and provides excellent adhesion for subsequent layers.

Characteristics

Viscosity : 9-12 sec. in DIN 4mm at 25°C.

Density : 1.04 ± 0.02 kg/l

Solid Content : 19-23%

VOC : Max 2%

Classification : Complies with the Environmental Protection Act of 1990.

Application

Preparation : Stir well and check before use.

Hardener : Not required

Thinner : Use water to adjust viscosity if required.

Viscosity : As delivered

Film Weight : Apply 40 - 60 g/m² one pass.

Drying :
12-15 sec at 120°C jet air with airspeed of 23 m/s.
50 sec at 150°C circulatory air with airspeed of 5-7 m/s and a circulatory to fresh air proportion 8:2.

Substrate : This product is specially formulated as stain to be applied on wooden substrates for subsequent coating with TEKNOS TREFFERT products.
Please consult our technical staff prior to other applications.

Storage

TECHNICAL DATASHEET

Description : **W/B STAIN BASE**

Product Number : **284-209-0000**

Shelf Life : 12 months

Conditions : Protect from sunlight and frost. Keep container tightly closed and in a well ventilated place. Keep away from sources of ignition, heat and oxidizing substances.

To be stored at 5-35 °C.

Delivery

Packaging : Available in 20 kg pails.

Delivery Time : Please allow 6 working days of production and transportation.

Quantity : Except for trial, minimum quantity is 100kg per individual product.

Cleaning : Clean equipment with water immediately after use.

Precautions : Refer to Safety Data Sheet.

Health & Safety : Refer to Safety Data Sheet.