

MOTIVO COLORATO

WATER-BORNE 1C COLOURED COATING

THE PRICE-PERFORMANCE WINNER

With MOTIVO COLORATO, almost any colour can be quickly and cost-effectively applied to surfaces. Good recoatability means it can also be used in combination with MOTIVO KLARLACK 2080 for top-class results. MOTIVO COLORATO is used mainly for interior furniture and doors, stairs and general joinery work.

DIVERSE PRODUCT LINE

The water-borne MOTIVO line for interiors is particularly quick drying. Thanks to optimum filling properties, the coloured coating is easily applied to open- and closed-pore woods and primed MDF boards. The perfectly matched product systems make it even more certain that the user achieves a high-quality application.

VERSIONS

MOTIVO COLORATO 2070 is a coloured, quick-drying top coat in all RAL and NCS S colours. MOTIVO COLORATO 2077 STRUKTUR is also a coloured coating in all RAL and NCS S colours, but in addition has a fine surface texture.



MAIN FEATURES

Good resistance to the effects of light

Easy to apply with very good levelling properties

Quick drying with good filling properties

Good mechanical resistance

MINERGIE-ECO® compatible

CONTACT US

Get expert advice on the use of MOTIVO COLORATO or other Teknos coating products. Our technical customer service is always at your disposal when it comes to developing optimum coating solutions and systems.



Our mission is to make the world last longer by providing smart, technically advanced paint and coating solutions to protect and prolong - always in close cooperation with our customers.

 **TEKNOS**

PRODUCT FACTS

MOTIVO COLORATO

1C WATER-BORNE COLOURED COATING

VERSIONS	MOTIVO COLORATO 2070-15 MOTIVO COLORATO 2070-30 MOTIVO COLORATO 2077-05 STRUKTUR
COLOURS	In compliance with RAL and NCS S shade cards
GLOSS LEVEL	Dull matt 05, matt 15, satin matt 30
APPLICATION	<ul style="list-style-type: none">▪ Gravity feed gun▪ Airless (airmix) spraying
CONTAINER SIZE	Paint: 2.7 l and 9 l

DRYING TIMES	
Dust dry after	30 minutes
Touch dry after	45 minutes
Sandable after	2 hours
Recoat after	2 hours
Fully dry after	10 days

COATING RECOMMENDATION MOTIVO COLORATO 2070

	MDF/HDF	FOIL-LAMINATED BOARDS	WOOD
PRIMER	HYDROFILL PREMIUM 6338-00	HYDROFILL PREMIUM 6338-00	MOTIVO COLORATO 2070
INTERMEDIATE SANDING	Grain 220-240	Grain 220-240	Grain 220-240
RECOATING	MOTIVO COLORATO 2070	MOTIVO COLORATO 2070	MOTIVO COLORATO 2070

COATING RECOMMENDATION MOTIVO COLORATO 2077 STRUKTUR

	MDF/HDF	FOIL-LAMINATED BOARDS
PRIMER	HYDROFILL PREMIUM 6338-00	HYDROFILL PREMIUM 6338-00
INTERMEDIATE SANDING	Grain 220-240	Grain 220-240
RECOATING	MOTIVO COLORATO 2077 STRUKTUR	MOTIVO COLORATO 2077 STRUKTUR

For further technical information refer to technical data sheets Nos. 2575 and 2577

WE MAKE THE WORLD LAST LONGER

TEKNOS GBI
7 LONGLANDS RD
BICESTER
OXON OX26 5AH
T 01869 208005

TEKNOS IRELAND
54 BALLYMOUGHAN RD
MAGHERAFELT
BT45 6HN
T 02879 301472

sales@teknos.co.uk
www.teknos.co.uk

 **TEKNOS**