

TEKNOCLEAN 1956-00 is a concentrated cleaning agent for removal of dust, insects and other pollutants that could serve as a basis for infestation by algae and fungi from coated surfaces.

TECHNICAL DATA

Type: Alkaline cleaning agent.

Volatile organic compound (VOC): See Safety Data Sheet.

Colour range: Colourless

APPLICATION DETAILS

Dosing: Light cleaning: 1 % = 1 dl per 8-10 l water (pH approx. 9)
Thorough cleaning: 5 % = 5 dl per 8-10 l water (pH approx.10)
or
Undiluted (pH approx.11)

Application: Is applied with brush, cloth or sponge.

After cleaning, rinse all surfaces thoroughly with clean water.

Use TEKNOCARE 4250-00 for the enhancement of possible dull coated surfaces.

Application conditions: Is applied in a suitable thinning or undiluted. Reaction time 0.5 – 5 min.

Please note when used undiluted the reaction time is very fast and it is important to rinse all surfaces thoroughly with clean water immediately after the cleaning.

To ensure suitability the product should be tested on a small, unnoticeable area of the surface to be treated.

Cleaning: The equipment is cleaned with water.

HEALTH AND SAFETY See Safety Data Sheet.

ADDITIONAL INFORMATION

Contents: Non-ionic surfactants: <5 %
Anionic surfactants: <5 %
EDTA and salts thereof: <5 %

Pack size: 1 l

Storage: The product must be stored at temperatures above 5 °C. Shelf life 2 years from production date in unopened package (see package). Keep containers tightly closed after use.