



TEKNOS PAINTS QUICK GUIDE

All tintable Teknos paints can be matched to any British standard colour including NCS, RAL, BS and our own range of popular shades, Colour Mode.

TEKNOSPRO 5/7/10



Emulsion, solvent free, Class 1 scrub rating, touch dry 30 mins, recoat 1hr. Available base 1 & 3.

Interior walls and ceilings

TIMANTTI 3



Adhesion primer, mildew resistant, most interior wall substrates, also can be used on galvanised metal (a/c pipes), touch dry 30 mins recoat 1hr. Base 1 only.

Interior walls and ceilings

TIMANTTI 7/20



Interior walls and ceilings Mildew resistant, class 1 scrub rating, touch dry 1hr, recoat 2hrs.

Interior walls and ceilings

TIMANTTI W



Moisture barrier good for use on most substrates, goes on light green, dries almost clear, touch dry 2hrs, overcoat 4hrs.

Interior walls and ceilings

TIMANTTI STOP



Stain block for soot, nicotine, water damage etc, flat matt finish, touch dry 1hr.

Interior walls and ceilings

TIMANTTI CLEAN



Anti-bacterial with BioCote® silver phosphate. Class 1 scrub rating, touch dry 1hr, recoat 3hrs, ideal for hospitals. Available in base 1 & 3.

Interior walls and ceilings

FUTURA AQUA 3



Adhesion primer, can be painted on all exterior and interior wood including furniture. Toy standard. Touch dry 1hr, overcoat 3hr. Available in base 1 & 3.

Interior/exterior wood | Interior galvanised metal

FUTURA AQUA 20/40/80



Very hard wearing topcoat for interior wood eg doors, windows, kitchens. Toy standard, marine equipment approval, touch dry 1hr, recoat 4hr. Available in base 1 & 3.

Interior/exterior wood | Interior galvanised metal

HELO AQUA 20/40/80



Polyurethane varnish for wood surfaces, toy standard. Touch dry & recoat 1 - 3hrs. Can be tinted. Use on floors, doors, trim, kitchen cabinets.

Interior and exterior wood

FERREX AQUA



Primer and rust inhibitor for Iron, steel etc adhesion primer for galvanised metal. Touch dry 3hrs, available in grey and white.

Interior and exterior metal

SILOKSAN FAÇADE



Silicate masonry paint, for lime substrate, use with Siloksan gel. Allows substrate to breathe and moisture to evaporate. Touch dry 30mins, recoat 2hrs. Base 1 & 3.

Exterior masonry

SILOKSAN GEL



Use with Siloksan Façade paint to improve adhesion to difficult substrates, will reduce amount of coats needed, comes in 1L tin only.

Exterior masonry

WOODEX AQUA BASE



Anti fungal preservative, non-film-forming protects against rot, mould, blue stain.

Exterior wood

WOODEX AQUA WOOD OIL



Non-film-forming, ideal for decking, UV protection when tinted, prevents cracking & moisture damage. Touch dry 4hrs fully dry 16hrs. Part of annual maintenance.

Exterior wood

WOODEX AQUA CLASSIC



Non-film-forming wood stain, UV protection when tinted, use on new wood and wood treated with a non-film-forming stain. Fully dry 16hrs.

Exterior wood

WOODEX AQUA SOLID



Opaque wood stain, ideal to go over previously stained wood, will give an even colour. Recoat in 12hrs, available in base 1 & 3.

Exterior wood