

TIMANTTI

Specialist interior paints



THE TIMANTTI RANGE

The TIMANTTI interior paints range includes water-borne paints for facilities that need extra durability on their painted surfaces or have problem areas that need special treatment. Key product features:

- High scrub ratings
- Water-borne
- Stain blockers
- Overcoat in 1-3 hours
- Semi-matt or full-matt
- Tintable
- Fire neutral TIMANTTI CLEAN
EN 13501-1: B-s1,d0
Classification for reaction to fire

TIMANTTI CLEAN



FEATURES: FIRE NEUTRAL, ANTIMICROBIAL INTERIOR PAINT, IDEAL FOR HOSPITALS AND CLASSROOMS



A water-borne acrylate dispersion paint for indoor use. For new primed and previously painted surfaces in dry, humid or wet spaces where high levels of hygiene are important.

It contains Biocote[®] silver phosphate glass anti-microbial technology that prevents microbial growth and it has a class 1 scrub-rating. TIMANTTI CLEAN has been classified for reaction to fire. It is fire neutral; it does not contribute to the spread of flame so is ideal for public

spaces such as hospitals, classrooms, indoor sports facilities and business premises.

It has a spreading rate of 6-8 m²/l. Suitable for brickwork, plaster, filler, concrete and building boards. Re-coat in 3hrs.

Available in semi matt. Tint from the Teknos Colour Mode range or to any British standard colour.

Pack sizes: 9L and 18L.

**FIRE NEUTRAL
PAINT
EN 13501-1:
B-s1,d0**

**ANTI-MICROBIAL
SEMI-MATT PAINT**

TIMANTTI 20



FEATURES: SEMI-MATT SPECIAL ACRYLATE MILDEW-RESISTANT PAINT.



Water-borne special acrylate paint for indoor walls and ceilings. Especially suitable for dry and humid spaces where good washability and abrasion resistance is required, e.g. kitchens, bathrooms, halls, staircases, kindergartens, schools, hospitals, food processing premises and other similar facilities. Mildew-resistant.

TIMANTTI 20 has a spreading rate of 6-8 m²/l. It is suitable for new primed

and previously painted concrete, plaster, filler, brick and building boards. Re-coat in 2hrs.

Available in semi matt. Tint from the Teknos Colour Mode range or to any British standard colour.

Pack sizes: 0.9L, 2.7L, 9L and 18L.

**MILDEW-RESISTANT
SEMI-MATT PAINT**

PAINTS FOR HIGH STRESS & HEAVY USE AREAS

TIMANTTI 3



FEATURES: ENHANCES THE DURABILITY OF TIMANTTI TOP COATS AND CAN BE USED AS A CEILING TOP COAT.



Water-borne acrylate based adhesion primer for walls and ceilings indoors, ideal for promoting the durability of Timantti top coats and other Teknos interior paints.

Can also be used as top coat on ceilings and for priming surfaces that are to be wallpapered.

This paint has a spreading rate of 5-8 m²/l.

Suitable for priming concrete, plaster, filler, brick, galvanised sheet metal and building board surfaces. Re-coat in 1hr.

Available in full matt in white. Can be tinted to light shades.

Pack sizes: 0.9L, 2.7L, 9L and 18L.

ADHESION
PRIMER

TIMANTTI STOP



FEATURES: AN INSULATION PRIMER THAT EFFECTIVELY BLOCKS AND COVERS STAINING.



A highly efficient water-borne insulation primer with excellent performance. For priming indoor walls and ceilings to insulate and fix discolouration caused by soot, nicotine or water damage.

Can be top coated with all Teknos interior paints.

Spreading rate of 5-8 m²/l.

Suitable for new primed and previously painted concrete, plaster, filler, brick and building board surfaces

Available in full matt in white. Can be tinted to light shades.

Pack sizes: 0.9L, 2.7L, 9L and 18L.

INSULATION
PRIMER

TIMANTTI W



FEATURES: WATER-BORNE MOISTURE SEALER FOR WET ROOMS AND INTERIORS PRONE TO DAMP.



Water-borne moisture sealer that forms a steam-proof film. For use as a moisture barrier on walls and ceilings in damp interiors and wet rooms. Two coats are applied, followed with a top coat from the TIMANTTI series.

Spreading rate of 4-8 m²/l. The colour is transparent green.

Suitable for concrete, filler and building

board surfaces, and glass fibre wall fabric glued with adhesive for moist areas. Approved by the Swedish Måleribranschens Våtrumskontroll (MVK) as part of a coatings system (with TIMANTTI 20) for wet rooms.

Pack sizes: 0.9L, 2.7L and 9L.

MOISTURE
SEALER

WE MAKE THE WORLD LAST LONGER

Teknos GBI is a leading supplier of water-based coatings which has specialised in paints for factory finished joinery for over 25 years. Our paints are high-quality, low odour with sustainability at their core. We are growing and now offer a wide range of decorative paints for professional decorators which are stocked by specialist merchants across the UK and ROI. Our portfolio of wet and powder coatings for metal is also expanding and provides coating solutions for a variety of machines, structures and components. Established in the UK since 1991, we are part of Teknos, a global company with operations in more than 20 countries across Europe, Asia and USA.

The Teknos Group has a unique history, experience and culture which are enshrined in the Teknos GBI approach. The company's values of creativity, persistence and fairness, permeate all we do so that our offering goes beyond paint; our professionalism and experience will solve your coatings problems. Our paints protect and prolong so that together, we can make the world last longer.

TEKNOS GBI (HEAD OFFICE)
BICESTER
T: +44 (0)1869 208005
SALES@TEKNOS.CO.UK

TEKNOS (IRELAND)
MAGHERAFELT
T: +44 (0)2879 301472
SALES.IRELAND@TEKNOS.CO.UK



WWW.TEKNOS.CO.UK

