

# TEKNOCLAD 3370

WATER-BORNE PRIMER / INTERMEDIATE / TOPCOAT

## DESIGNED FOR HIGH SPEED FINISHING

Water-borne, industrial primer, intermediate and topcoat for exterior wooden cladding with good anti-blocking properties, which makes it perfect for stacking.

TEKNOCLAD 3370 can be applied by all conventional hand spraying and automated systems.

## KEY BENEFITS

Long-term protection against weathering

Primer, intermediate and topcoat in one, saving you time and resources

Anti-blocking properties, enabling high-speed finishing and stacking

Dry to handle in 60 minutes and fit for sanding and overcoating in 2 hours (+23°C / 50% RH) - drying times can be reduced even further using special drying systems to force drying.

Suitable cladding boards: Hardwood, Softwood, Modified wood and Thermally Modified wood



### TRANSLUCENT OR OPAQUE?

TEKNOCLAD 3370 is available in a wide range of both translucent and opaque colours

TEKNOS GBI  
Unit 7 Longlands Road  
Bicester  
Oxfordshire, OX26 5AH  
T +44 (0) 1869 208 005  
sales@teknos.co.uk

TEKNOS Ireland  
54 Ballymoughan Road,  
Magherafelt  
BT45 6HN  
T +44 (0) 2879 30147  
sales.ireland@teknos.co.uk



WE MAKE THE WORLD  
LAST LONGER

[www.teknos.co.uk](http://www.teknos.co.uk)

# HIGH-SPEED FINISHING LINES

## ANTI-BLOCKING PROPERTIES

TEKNOCLAD 3370 has excellent anti-blocking properties and can be applied with automated spray lines, meaning you can coat and store cladding boards much faster.

Boasting a dry to handle time of just 60 minutes and being suitable for sanding and overcoating in 2 hours (+23° C / 50% RH). TEKNOCLAD drying times can be reduced even further using special drying systems to force drying.

For more information on how to achieve this, contact your local Teknos coating expert.



TEKNOS UK  
Unit 7 Longlands Road  
Bicester  
Oxfordshire, OX26 5AH  
T +44 (0) 1869 208 005  
sales@teknos.co.uk

TEKNOS Ireland  
54 Ballymoughan Road,  
Magherafelt  
BT45 6HN  
T +44 (0) 2879 30147  
sales.ireland@teknos.co.uk



The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.